TEREON Technology (Pty) Ltd

Email: Gideon@tereon.tech Plot 19, Rietfontein Rd, Agricultural Holdings, Pretoria East

Web: www.tereon.tech GPS: -25.872074, 28.332073



TACET SILENCER / SUPRESSOR TECHNICAL WARRANTY INFORMATION

TACET Silencers are constructed from a combination of Aluminum and Seamless Hydraulic Steel Tube. The burst chamber is capable of a combined pressure resistance of over 415Bar. This is a safety factor of 3, for the industry standard of 137Bar explosive pressure in the burst chamber of the top range standard calibers.

Materials and Workmanship Warranty – 2 years or 2000 rounds (whichever comes first).

TACET (TEREON) Suppressors/Silencers should only be fitted to your rifle by suitably qualified or trained gunsmiths. TEREON accepts no liability or warranty for any work (or damage resulting) from third parties, or incorrect installation.

Maximum operating temperature for TACET (TEREON) models is 160 deg C. Overheating the unit above this temperature will void the warranty. On over-barrel units we recommend not heating above 100 deg. C at the rear bushing location.



- Normal wear & tear.
 - Damage from using goods for a purpose for which they were not designed.
 - Damage from neglect or careless storage.
 - Damage from having unauthorized repairs carried out.

This warranty does not cover damage to the silencer and/or host firearm resulting in whole or in part from criminal, abusive or negligent use, improper or careless handling, unauthorized modifications, defective, improper hand loaded or reloaded ammunition, or neglect. Any repairs to the unit made necessary by these factors will be invoiced to the owner.

